

Accessories: Sprayer

High-efficiency, long-lasting **central pivot irrigation** application equipment for low-pressure pumps.

The Sprayer can uniformly wet an area with a diameter of 8-12m.

- 360-degree water distribution
- 80% uniformity of water distribution
- Min pressure: 1.5m
- Max pressure: 5m
- Min to max flow: 750 – 2000 L/h
- 0.75-inch hose connection
- Max ground gradient of 1:6
- 4-6m radius, 1.8m total height



OPTIMAL SPRAYERS

| Pump Output (L/h) | Minimum number | Maximum number |
|-------------------|----------------|----------------|
| 3850 | 2 | 7 |
| 3300 | 2 | 6 |
| 2750 | 2 | 5 |
| 2200 | 2 | 4 |
| 1650 | 1 | 3 |
| 1100 | 1 | 2 |
| 550 | 1 | 1 |

PORTABILITY

The Sprayer can be dismantled and stored in a package of 1.95 x 0.17 x 0.17m, weighing 12kg.


The Sprayer's wetted area is 50m² to 110m² and it is portable to allow easy irrigation of larger fields.

PIPE ATTACHMENT

A tripod can be used to place the Sprayer in the field or a direct connection to a buried pipe system.

DISTRIBUTORS

To discuss ordering Sprayers - please contact:
sales@futurepump.com



SPRAYER SET UP

