

## Accessories: Sprayer

High-efficiency, long-lasting **central pivot irrigation** application equipment for low-pressure pumps.

The Sprayer can uniformly wet an area with a diameter of 8-12m.

- 360-degree water distribution
- 80% uniformity of water distribution
- Min pressure: 1.5m
- Max pressure: 5m
- Min to max flow: 750 – 2000 L/h
- 0.75-inch hose connection
- Max ground gradient of 1:6
- 4-6m radius, 1.8m total height



### OPTIMAL SPRAYERS

Pump Output (L/h)	Minimum number	Maximum number
3850	2	7
3300	2	6
2750	2	5
2200	2	4
1650	1	3
1100	1	2
550	1	1

### PORTABILITY

The Sprayer can be dismantled and stored in a package of 1.95 x 0.17 x 0.17m, weighing 12kg.


The Sprayer's wetted area is 50m<sup>2</sup> to 110m<sup>2</sup> and it is portable to allow easy irrigation of larger fields.

### PIPE ATTACHMENT

A tripod can be used to place the Sprayer in the field or a direct connection to a buried pipe system.

### DISTRIBUTORS

To discuss ordering Sprayers - please contact:  
[brian.marsh@futurepump.com](mailto:brian.marsh@futurepump.com)



### SPRAYER SET UP

